

**Amendments to the Claims:**

**This listing of claims will replace all prior versions and listings of claims in the application.**

**Listing of Claims:**

Claim 1 (currently amended): A multi-component electrically conductive fiber comprising:

a first component comprising a first polyester having dispersed therein an electrically conductive material, wherein the first polyester has a first melting temperature; and

a second component comprising a second polyester which is not the same as the first polyester, wherein the second polyester has a second melting temperature; wherein the difference between the first melting temperature and the second melting temperature is ~~not more than about~~ less than 10° C.

Claim 2 (previously presented): The multi-component electrically conductive fiber of claim 1 wherein the first polyester is polyethylene terephthalate or other copolymer of terephthalic acid or a lower alkyl ester thereof, a C2-C10 aliphatic or cycloaliphatic diol, and one or more modifiers selected from the group consisting of diols, diacids, and diesters.

Claim 3 (previously presented): The multi-component electrically conductive fiber of claim 2 wherein the one or more modifiers is selected from the group consisting of ethylene glycol, diethylene glycol, propylene glycol, butanediol, cyclohexanedimethanol, adipic acid, maleic acid, and phthalic acid.

Claim 4 (withdrawn): The multi-component electrically conductive fiber of claim 1 wherein the first polyester is a polybutylene terephthalate (PBT) based polymer.

Claim 5 (withdrawn): The multi-component electrically conductive fiber of claim 1

wherein the first polyester is a polytrimethylene terephthalate (PTT) based polymer.

Claim 6 (original): The multi-component electrically conductive fiber of claim 1 wherein the second polyester is polybutylene terephthalate (PBT).

Claim 7 (withdrawn): The multi-component electrically conductive fiber of claim 1 wherein the second polyester is polytrimethylene terephthalate (PTT).

Claim 8 (original): The multi-component electrically conductive fiber of claim 1 wherein the electrically conductive material comprises carbon black.

Claim 9 (withdrawn and currently amended): A method of preparing a drawn multi-component electrically conductive fiber, the method comprising:

preparing an undrawn fiber by co-extruding a first component comprising a first polyester having dispersed therein an electrically conductive material and a second component comprising a second polyester which is not the same as the first polyester, wherein the first polyester has a first melting temperature and the second polyester has a second melting temperature, wherein the difference between the first melting temperature and the second melting temperature ~~does not exceed about~~ is less than 10° C.; and drawing the undrawn fiber while applying heat to form a drawn fiber.

Claim 10 (withdrawn): The method of claim 9 wherein the drawn fiber has an electrical conductivity which is not less than the electrical conductivity of the undrawn fiber.

Claim 11 (withdrawn): The method of claim 9 wherein the first polyester is more amorphous than the second polyester.

Claim 12 (withdrawn): The method of claim 9 wherein the electrical conductivity of the

drawn fiber is greater than the electrical conductivity of the undrawn fiber.

Claim 13 (withdrawn): The method of claim 9 wherein the first polyester is a copolymer of terephthalic acid or a lower alkyl ester thereof, a C2-C10 aliphatic or cycloaliphatic diol, and one or more modifiers selected from the group consisting of diols, diacids, and diesters.

Claim 14 (withdrawn): The method of claim 13 wherein the one or more modifiers is selected from the group consisting of ethylene glycol, diethylene glycol, propylene glycol, butanediol, cyclohexanedimethanol, adipic acid, maleic acid, and phthalic acid.

Claim 15 (withdrawn): The method of claim 9 wherein the first polyester is a polybutylene terephthalate (PBT) based polymer.

Claim 16 (withdrawn): The method of claim 9 wherein the first polyester is a polytrimethylene terephthalate (PTT) based polymer.

Claim 17 (withdrawn): The method of claim 9 wherein the second polyester is polybutylene terephthalate (PBT).

Claim 18 (withdrawn): The method of claim 9 wherein the second polyester is polytrimethylene terephthalate (PTT).

Claim 19 (withdrawn): The method of claim 9 wherein the electrically conductive material comprises carbon black.

Claim 20 (withdrawn): A method of preparing a drawn bi-component electrically conductive fiber, the method comprising:

preparing an undrawn fiber by co-extruding (i) an electrically conductive first component comprising a copolymer of terephthalic acid or a lower alkyl ester thereof, a

C2-C10 aliphatic or cycloaliphatic diol, and one or more modifiers selected from the group consisting of ethylene glycol, diethylene glycol, propylene glycol, butanediol, cyclohexanedimethanol, adipic acid, maleic acid, and phthalic acid; the copolymer having dispersed therein electrically conductive carbon black, and (ii) a non-conductive second component comprising polybutylene terephthalate; and

drawing the undrawn fiber at a temperature from about 80 to about 190° C. to form a drawn fiber;

wherein the drawn fiber has an electrical conductivity which is not less than the electrical conductivity of undrawn fiber.

Claim 21 (withdrawn): The method of claim 20 wherein the drawn fiber has an electrical conductivity which is greater than the electrical conductivity of the undrawn fiber.